

Description

NP-9X

NP-9X is the successor of the NP-L7S, the industry standard NP-style battery for powering audio equipment. It now features 96Wh, two D-Tap outputs, and a 5 LED power indicator. One of the D-Tap port is a D-Tap Advanced, which can also be a charge port when used with the IDX VL-DT1 charger. NP-9X is still compatible with all current accessories and chargers like the JL-2PLUS.



Features



- 96Wh (14.4V / 6.6Ah) capacity
- Meets $\leq 100\text{Wh}$ passenger aircraft carry-on requirement
- 2x D-Tap outputs
- Charging via D-Tap (*compatible only with IDX VL-DT1 D-Tap charger*)
- 5 LED power indicator (*two-step LED allows for displaying 10% increments*)
- Compatible with all current accessories and chargers



Specifications



Capacity:	96Wh (14.4V / 6.6Ah)
Max Output Voltage:	16.8V
Nominal Voltage:	14.4V
Max Draw:	4.6A / 50W (<i>total of main connector and D-Taps</i>)
End Voltage:	11V
Power Outputs:	(1) D-Tap, (1) D-Tap Advanced
* D-Tap:	50W each
* D-Tap Advanced:	Compatible only with IDX VL-DT1 charger
Additional Feature:	5 LED Power Indicator
Battery Protection:	Over-charge/discharge/current, Thermal
Ambient Temperature:	To charge: 0°C ~ 40°C
	To discharge: -20°C ~ 45°C
	To store: -20°C ~ 65°C
Dimensions:	185(W) x 71(H) x 25(D) mm
Weight:	520 grams approx.

IDX reserves the right to change the specifications contained herein without notice.